

Product Technical Statement

Product Description: Linea™ Oblique™ Weatherboard is a rusticated profile weatherboard wall cladding manufactured using low density fibre cement formulation.

Scope of Use: Linea Oblique Weatherboard is suitable for use as external wall cladding on residential buildings within the scope of E2/AS1 or light weight residential/commercial buildings with design wind pressure of 2.5kPa (ULS) covered by a specific engineering design (SED). It must be fixed over a timber cavity batten that is nominal 20mm thick and used for buildings that are exposed to wind pressures up to 2.5kPa (ULS).

Linea Oblique Weatherboard is also suitable for use in fire rated systems.

Limitations: Linea Oblique Weatherboard cladding must not be used in curved wall applications or in situations where it stays in contact with ground moisture.

Compliance with the NZBC: The following clauses of the NZBC are applicable to Linea Oblique Weatherboard cladding and it complies with these requirements as explained below;

Structure - B1: Uniform wind face load tests have been completed at BRANZ and the suitability of Linea Oblique Weatherboard and its fixings has been verified to meet wind pressure requirement in various wind zones classified in NZS 3604 and SED wind zone up to wind pressure of 2.5kPa and complies with the requirements of B1.3.1, B1.3.2 and B1.3.4.

Durability - B2: Linea Oblique Weatherboard has been assessed at a NATA accredited James Hardie laboratory in accordance with AS/NZS 2908.2 and meets the durability performance requirements as per B2.3.1(a) and B2.3.2 of this clause.

Fire Performance - C: Linea Oblique Weatherboard has been assessed and is classified as non-combustible material and is suitable for use on external walls close to boundaries.

External Moisture - E2: Linea Oblique Weatherboard cavity cladding as per its details has been assessed for weathertightness as per E2/M1 (as contained within NZBC Clause E2).

Hazardous Building Materials - F2: Linea Oblique Weatherboard complies with the requirements of F2.3.1 and will not present a health hazard when handled as per its technical specifications.

Energy Efficiency - H1: Linea Oblique Weatherboard clad walls constructed using bulk insulation meets the construction R-Value requirements as per Table 1 of Clause H1.

Linea Oblique Weatherboard has a BRANZ appraisal for horizontal and vertical cavity construction method. Refer to BRANZ appraisal No. 896 and 897 at www.branz.co.nz

Linea Oblique Weatherboard has also been assessed under the product certification scheme by MBIE and is covered under CodeMark. Refer to CodeMark certificate; www.building.govt.nz

Installation: Linea Oblique Weatherboard must be installed in accordance with the current Linea Oblique Weatherboard Horizontal Installation Technical Specification/ Linea Oblique Weatherboard Vertical Installation Technical Specification. The specification and details are available at James Hardie web site www.jameshardie.co.nz or Ask James Hardie™ at 0800 808 868 for further information.

Warranty: Linea Oblique Weatherboard has a product warranty of 25 years when installed and maintained as per the current technical specification.

Copy right April 2019. © James Hardie New Zealand Limited. ™ and ® Denotes a trademark or registered trademark owned by James Hardie Technology Limited