

Product Technical Statement

Product Description:

Hardie™ Flex Eaves Lining is a 4.5mm thick fibre cement sheet for soffit lining.

Scope of Use:

Hardie™ Flex Eaves Lining is suitable for use as a soffit lining in residential or light commercial buildings.

Limitations:

Hardie™ Flex Eaves Lining is only for use in external soffit applications up to and including Very High wind zone.

Compliance with the NZBC:

The following clauses of the NZBC are applicable to Hardie™ Flex Eaves Lining and it meets these requirements as explained below.

Structure - B1: Hardie™ Flex Eaves Lining installed as per its installation manual meets the requirements of Clause B1.3.1, B1.3.2 and B1.3.4.

Durability - B2: Hardie™ Flex Eaves Lining are manufactured in accordance with the AS/NZS 2908.2 and meets the durability performance requirements of Clause B2.3.1(d) and B2.3.2.

External Moisture - E2: Hardie™ Flex Eaves Lining installed as per its installation manual meets the requirements of Clause E2.

Hazardous Building Materials - F2: Hardie™ Flex Eaves Lining complies with the requirements of Clause F2.3.1 and will not present a health hazard when handled as per its technical specifications.

Installation:

Hardie™ Flex Eaves Lining must be installed in accordance with the Eaves and Soffits Installation Manual by James Hardie. The specifications are available online at www.jameshardie.co.nz or Ask James Hardie™ at 0800 808 868 for further information.

Maintenance:

Hardie™ Flex Eaves Lining used in soffit applications must be cleaned/washed regularly to meet the durability requirements

Warranty:

Hardie™ Flex Eaves Lining has a product warranty of 15 years when installed and maintained as per the current installation manual.

Hardie™ Flex Eaves Lining is not subject to a warning or ban under section 26 of the Building Act.

Hardie™ Flex Eaves Lining is manufactured in Australia.