

# Oblique™ Weatherboard







# Oblique™ Weatherboard

## A MODERN CLASSIC

Embrace design diversity with Oblique™ Weatherboard, choose to personalise your home using a blend of colours and lines. Find inspiration in the different elements Oblique™ Weatherboard brings to external walls for dynamic and unique building facades that really stand out.

Oblique™ Weatherboard comes in two widths and can be used in both horizontal and vertical applications enabling you to create a range of different looks and designs.

Oblique™ Weatherboard can be used to create colourful feature walls, full cladding for new builds, cladding for additions and renovations and internal feature walls. It is lightweight and durable, making it ideal for overhangs, protective cantilevers and other striking architectural features.

Oblique™ Weatherboard gives you classic and contemporary design solutions at your fingertips, all with the added benefits of fibre cement.



# What is fibre cement?

Engineered for durability, fibre cement is resistant to fire, rot resistant and resistant to moisture damage, making it an ideal low maintenance building material. Fibre cement offers both contemporary and flexible design options and is used by many New Zealanders to create stunning facades.

The simple combination of wood cellulose fibre, sand, cement and water, give the product its strength to stand the test of time.

# Profiles & Sizes



## 200mm WIDE

This width captures that timeless, classic charm of the rusticated weatherboard look. It's also an ideal way to make smaller wall spaces look larger.



## 300mm WIDE

For a modern twist of a classic profile, use the 300mm wide weatherboard. Ideal for larger walls, it creates a look that's confident and contemporary.



## COMBINATION

Try combining the 200 and 300mm widths vertically to create an architectural look that's modern and unique.

LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)
2750	200	14
2750	300	14
4200	200	14
4200	300	14

Oblique™ Weatherboard is a ship-lapped weatherboard with a splayed edge and is available in two different profiles.





# Features & Benefits



## WEATHER RESISTANT

Engineered to stand up to New Zealand's harsh conditions



## RESISTANT TO MOISTURE DAMAGE



## FIRE RESISTANT

Fire protection with up to 60 minute fire resistance when used as part of a fire rated system



## EASY TO PAINT

Can be painted a wide variety of colours, including the darker shades



## LIGHT WEIGHT

Classified as a lightweight cladding under NZ Building Code



## EASY TO CLEAN

Fast and effective using low pressure water and a brush



## COMPLIANCE

BRANZ appraised and CodeMark certified



## COST EFFECTIVE

Cost effective and long-lasting



## 25 YEAR WARRANTY

Backed with a 25 year product warranty

# Corner options



## ALUMINIUM TRIM

Use the aluminium trim to achieve a sleek modern corner. The trim comes ready to paint, allowing you to create an almost seamless finish to your final design.

## HARDIE™ AXENT™ TRIM

Hardie™ Axent™ Trim made from fibre cement, is an easy way to create the classic feature corners often seen on traditional New Zealand homes.

The 19mm thickness of Hardie™ Axent™ Trim helps create the impression of solidness, and it's crisp, clean edges highlight frames and openings.

With performance benefits that match your cladding, Hardie™ Axent™ Trim is resistant to fire, rot resistant, resistant to damage from moisture, and can be painted in a wide variety of colours.







# Care & Maintenance

**With minimal maintenance you can keep your home looking like new. The following are the best practices for this product to improve its longevity and performance.**

- Washing down your exterior every 6-12 months using low pressure water and a brush, and every 3-4 months in extreme coastal conditions (such as high winds and sea spray)
- Clean out your gutters, downpipes and overflow pipes as required
- Cut back vegetation and landscaping which is too close to or touching the Oblique™ Weatherboard
- Re-applying exterior protective finishes. Always refer to the paint manufacturer for re-coating requirements
- Maintaining the exterior envelope and connections including joints, penetrations, flashings and sealants
- The clearances between the bottom edge of the Oblique™ Weatherboard and the ground must always be maintained





[jameshardie.co.nz](https://jameshardie.co.nz)



For more information, warnings and warranties please see our website and review the relevant installation and technical guides. James Hardie Durability-when installed and maintained correctly in accordance with James Hardie's literature, current at the time of installation, James Hardie products are resistant to fire, rot resistant and resistant to moisture damage. ©2023 James Hardie New Zealand Limited 0800 808 868. ™ and © denotes a trademark and registered mark owned by James Hardie Technology Ltd.