

Oblique™ Weatherboard



A modern, two-story house with a dark, textured facade made of Oblique Weatherboard. The house features large windows and a flat roof. In the foreground, there is a swimming pool with water spraying upwards, creating a dynamic scene. The sky is clear and blue.

Oblique™ Weatherboard

A MODERN CLASSIC

Embrace design diversity with Oblique™ Weatherboard, choose to personalise your home using a blend of colours and lines. Find inspiration in the different elements Oblique™ Weatherboard brings to external walls for dynamic and unique building facades that really stand out.

Oblique™ Weatherboard comes in two widths and can be used in both horizontal and vertical applications enabling you to create a range of different looks and designs.

Oblique™ Weatherboard can be used to create colourful feature walls, full cladding for new builds, cladding for additions and renovations and internal feature walls. It is lightweight and durable, making it ideal for overhangs, protective cantilevers and other striking architectural features.

Oblique™ Weatherboard gives you classic and contemporary design solutions at your fingertips, all with the added benefits of fibre cement.

What is fibre cement?

Engineered for durability, fibre cement is fire resistant, rot resistant and resistant to moisture damage, making it an ideal low maintenance building material. Fibre cement offers both contemporary and flexible design options and is used by many New Zealanders to create stunning homes.

The basic composition of Hardie™ fibre cement building products is Portland cement, ground sand, cellulose fibre, water and proprietary additives, which give the product its strength to stand the test of time.



Global GreenTag™ GreenRate™ Level A and Product Health Declaration™ PHD Platinum Health mean our products have passed the world's toughest standards for health, eco performance and safety.

Profiles & Sizes



200mm WIDE

This width captures that timeless, classic charm of the rusticated weatherboard look. It's also an ideal way to make smaller wall spaces look larger.



300mm WIDE

For a modern twist of a classic profile, use the 300mm wide weatherboard. Ideal for larger walls, it creates a look that's confident and contemporary.



COMBINATION

Try combining the 200 and 300mm widths vertically to create an architectural look that's modern and unique.

LENGTH (mm)	WIDTH (mm)	THICKNESS (mm)
3000	200	14
3000	300	14
4200	200	14
4200	300	14

Oblique™ Weatherboard is a ship-lapped weatherboard with a splayed edge and is available in two different profiles.



Features & Benefits



WEATHER RESISTANT

Engineered to stand up to New Zealand's harsh conditions



RESISTANT TO MOISTURE DAMAGE



FIRE RESISTANT

Fire resistance with up to 60 minute fire resistance rating when used as part of a fire rated system



EASY TO PAINT

Can be painted a wide variety of colours, including the darker shades



LIGHT WEIGHT

Classified as a lightweight cladding under NZ Building Code



EASY TO CLEAN

Fast and effective using low pressure water and a brush



COMPLIANCE

BRANZ appraised and CodeMark certified



COST EFFECTIVE

Cost effective and long-lasting



25 YEAR WARRANTY

Backed with a 25 year product warranty

Corner options



ALUMINIUM TRIM

Use the aluminium trim to achieve a sleek modern corner. The trim comes ready to paint, allowing you to create an almost seamless finish to your final design.

HARDIE™ AXENT™ TRIM

Hardie™ Axent™ Trim made from fibre cement, is an easy way to create the classic feature corners often seen on traditional New Zealand homes.

The 19mm thickness of Hardie™ Axent™ Trim helps create the impression of solidness, and it's crisp, clean edges highlight frames and openings.

With performance benefits that match your cladding, Hardie™ Axent™ Trim is resistant to fire, rot resistant, resistant to damage from moisture, and can be painted in a wide variety of colours.





Care & Maintenance

With minimal maintenance you can keep your home looking like new. The following are the best practices for this product to help improve its longevity and performance.

- Washing down your exterior every 6-12 months using low pressure water and a brush, and every 3-4 months in extreme coastal conditions (such as high winds and sea spray)
- Clean out your gutters, downpipes and overflow pipes as required
- Cut back vegetation and landscaping which is too close to or touching the Oblique™ Weatherboard
- Re-applying exterior protective finishes. Always refer to the paint manufacturer for re-coating requirements
- Maintaining the exterior envelope and connections including joints, penetrations, flashings and sealants
- The clearances between the bottom edge of the Oblique™ Weatherboard and the ground must always be maintained



jameshardie.co.nz



For more information, warnings and warranties please see our website and review the relevant installation and technical guides. When installed and maintained correctly in accordance with James Hardie's literature, current at the time of installation, James Hardie products are fire resistant, rot resistant and resistant to moisture damage.
©2025 James Hardie New Zealand Limited 0800 808 868. ™ and ® denotes a trademark and registered mark owned by James Hardie Technology Ltd.